

Rider seated lowlifter truck 3.0 ton

BT levio

R-series

LRE300

LRE300T



TOYOTA

MATERIAL HANDLING



SALES, SERVICE, PARTS

Rider seated lowlifter

Specifications					LRE300	LRE300T
Identification	1.1	Manufacturer			Toyota	Toyota
	1.2	Model			LRE300	LRE300T
	1.3	Drive			Electric	Electric
	1.4	Operator type			Seated	Seated
	1.5	Load capacity/rated load	Q	kg	3000	3000
	1.6	Load centre	c	mm	600	600
	1.8	Load distance, back of fork to bogie wheel centre	x	mm	1852/2352/2682	1852/2352/2682
Weight	2.1	Service weight without battery		kg	1720	1900
	2.2	Axle load, with load, drive/castor/fork wheel		kg	3300/2720	3490/3030
	2.3	Axle load, without load, drive/castor/fork wheel		kg	2430/590	2830/680
Wheels	3.1	Drive/castor/fork wheel			Polyurethane	Polyurethane
	3.2	Wheel size, front		mm	Ø 90	Ø 90
	3.3	Wheel size, rear		mm	Ø 350	Ø 350
Dimensions	4.2	Height	h_{15}	mm	1800	2115
	4.4	Lift	h_3	mm	110	110
		Lift height	h_{23}	mm	200	200
	4.8	Height of drivers seat	h_7	mm	1270	1585
	4.15	Height, fork lowered	h_{13}	mm	90	90
	4.19	Overall length	l_1	mm	3670	3670
	4.20	Length to face of forks	l_2	mm	1280	1280
	4.21	Overall width	b_1	mm	1000	1000
	4.22	Fork dimensions	e/l	mm	195/2390 ¹⁾	195/2390 ¹⁾
	4.25	Width over forks	b_5	mm	550/560/680	550/560/680
	4.32	Ground clearance, centre of wheelbase	m_1	mm	30	30
4.35	Turning radius	W_a	mm	3150	3150	
Perf.	5.1	Travel speed, with/without load		km/h	13,3/15,1	18,0/19,9
	5.10	Service brake			Electric	Electric
Electric motor	6.1	Drive motor rating S2 60 min		kW	9,0	7,5 x 2
	6.2	Lift motor rating at S3 4%		kW	2,0	2,0
	6.4	Battery voltage/nominal capacity K_s		V/Ah	48/840	48/840
	6.5	Battery weight		kg	1330	1600
Others	8.1	Type of drive control			Stepless	Stepless
	8.6	Steering			360° electrical	360° electrical

1) Other alternatives are available



All data are based on table configuration. Other configurations may give other values.

Truck performance and dimensions are nominal and subject to tolerances.

Toyota Material Handling Manufacturing Sweden AB products and specifications are subject to change without notice.

Dimensional drawings

BT levio



Truck features:

- High performance models
- Twin drive wheels
- Electronic steering
- 360° progressive steering
- Automatic deceleration
- BT Access control
- Driver detection system
- Adjustable seat
- Adjustable steering wheel
- Easy access for maintenance



TMHE-Toyota Material Handling Europe — 747301-040, version 3, 2019-07-29

TOYOTA

MATERIAL HANDLING